Response to Office Action Mailed June 29, 2006

Serial No.:

10/789,859

Filing Date: February 27, 2004

I. Amendments to the Claims

1. (Currently Amended) A table comprising:

a table top constructed from plastic, the table top including an upper surface and a lower surface that is spaced apart from the upper surface;

a drawer slidably connected to the lower surface of the table top;

at least two pairs of leg receiving recesses disposed on the underside of the table top;

a single support assembly that is sized and configured to support the table top above a

surface, the single support assembly being capable of moving between an extended position

in which the single support assembly supports the table top above the surface and a collapsed

position to facilitate storage of the table, the single support assembly including only two legs,

the single support assembly comprising:

a first leg including a body portion and an upper portion, the upper portion of the first leg being sized and configured to be selectively received and retained within

one of the pairs of leg receiving recesses; and

a second leg including a body portion and an upper portion, the upper portion

of the second leg being sized and configured to be selectively received and retained

within another of the pairs of leg receiving recesses, the first leg and second leg being

pivotally interconnected to form a generally X-shaped configuration.

2

Response to Office Action Mailed June 29, 2006

Serial No.:

10/789,859

Filing Date: February 27, 2004

The table as in Claim 1, wherein the upper portion of the first leg can 2. (Original) be selectively removed from one of the leg receiving recesses and received within another of the leg receiving recesses to allow a height of the table to be adjusted.

- 3. (Original) The table as in Claim 1, wherein the length of the upper portion of the first leg is adjustable in length between a first position in which the first leg can be inserted into a desired pair of leg receiving recesses and a second position in which the first leg can be secured within a desired pair of leg receiving recesses.
- (Currently Amended) The personal table as in Claim 1, further comprising a opening 4. integrally formed in a generally downwardly lip formed in the table top, the opening being sized and configured to receive at least a portion of the first leg and the second leg when the first leg and second leg are in a collapsed position.

Response to Office Action Mailed June 29, 2006

Serial No.:

10/789,859

Filing Date:

February 27, 2004

5. (Currently Amended) A table comprising:

a table top constructed from plastic, the table top including a lower surface and an

upper surface;

a drawer connected connect to the table top;

a first pair of leg receiving recesses, a second pair of leg receiving recesses and a third

pair of leg receiving recesses disposed on the underside of the table top;

a first leg including an upper portion that is sized and configured to be connected to

the first pair of leg receiving recesses recess;

a second leg including an upper portion that is adjustable in length between an

extended position and a collapsed position, the upper portion of the second leg being sized

and configured to be connected to the second pair of leg receiving recesses;

wherein the second leg can be disconnected from the second pair of leg receiving

recesses when the upper portion of the second leg is in the collapsed position and selectively

connected to the third pair of leg receiving recesses when the upper portion of the second leg

is in the extended position to change a height of the table.

6. (Original) The table as in Claim 5, wherein the first leg and the second leg are

pivotally connected in a generally X-shaped configuration.

7. (Currently Amended) The table as in Claim 5, further comprising an opening formed

in a side wall of the table top; and further comprising a first position in which the first leg and the

4

Response to Office Action Mailed June 29, 2006

Serial No.:

10/789,859

Filing Date: February 27, 2004

second leg extend generally away from the table top to facilitate use of the table and a second position in which the first leg and the second leg are positioned generally proximate the table top in a collapsed position; wherein at least a portion of the first leg and at least a portion of the second leg are being disposed within the opening in the side wall when the legs are in the second position.

- 8. The table as in Claim 5, further comprising a trigger mechanism (Original) attached to the upper portion of the second leg, the trigger mechanism being sized and configured to assist in moving the upper portion of the second leg between the extended position and the collapsed position.
- The table as in Claim 5, further comprising one or clips attached to a 9. (Original) r lower portion of the table top, the clips being sized and configured to retain the first leg and the second leg in a collapsed position.

Serial No.: 10/789,859

Filing Date: February 27, 2004

10. (Currently Amended) A table comprising:

a table top constructed from blow-molded plastic, the table top including a generally hollow interior portion, a lower surface, and an upper surface that is spaced apart from the lower surface, and a hollow interior portion that is formed during the blow-molding process, the hollow interior portion being at least partially disposed between the upper surface and the lower surface;

a frame connected to the lower surface of the table top, the frame including a plurality of pairs of leg receiving recesses;

a drawer slidably connected to the frame;

a single support assembly that is sized and configured to be selectively connected to the leg receiving recesses of the frame, the support assembly including a first leg and a second leg that are pivotally connected, the first leg and second leg being movable between a first position in which the first leg and the second leg have a generally X-shaped configuration and a second position in which the first leg and the second leg are in a collapsed configuration.

of leg receiving recesses formed in the table top, the first leg including an upper portion that is sized and configured to be selectively received within one of the pairs of leg receiving recesses in the frame and the table top, and the second leg including an upper portion that is sized and configured to be selectively received within another of the pairs of the leg receiving recesses in the frame and the

Response to Office Action Mailed June 29, 2006

Serial No.:

10/789,859

Filing Date:

February 27, 2004

table top.

12. (Original) The table as in Claim 10, wherein the first leg can be selectively

removed from one of the pairs of leg receiving recesses and received within another of the pairs of

leg receiving recesses to allow a height of the personal table to be adjusted.

13. (Original) The table as in Claim 10, wherein the length of the upper portion of the

first leg is adjustable in length between a first position in which the first leg can be inserted into a

desired pair of leg receiving recesses and a second position in which the first leg can be secured

within a desired pair of leg receiving recesses.

14. (Currently Amended) The table as in Claim 10, further comprising an a opening

integrally formed in a generally downwardly lip of formed in the table top during the blow-molding

process, the opening being sized and configured to receive at least a portion of the first leg and the

second leg when the first leg and second leg are in a collapsed position.

15. (Currently Amended) The table as in Claim 10, wherein an upper portion of the first

leg can be selectively removed from one of the pairs of leg receiving recesses and received within

another of the pairs of leg receiving recesses to allow a height of the personal table to be adjusted.

7

Response to Office Action Mailed June 29, 2006

Serial No.:

10/789,859

Filing Date: February 27, 2004

The table as in Claim 10, wherein the length of an upper portion of the \16. (Original) first leg is adjustable in length between a first position in which the first leg can be inserted into a desired pair of leg receiving recesses and a second position in which the first leg can be secured within a desired pair of leg receiving recesses.

(Currently Amended) A personal table that is intended to be used by a single user and 17. the height of the personal table is capable of being adjusted, the personal table comprising:

a table top constructed from plastic, the table top including an upper surface and a lower surface;

a drawer slidably connected to the table top;

a plurality of leg receiving recesses integrally formed in the table top as part of a unitary, one-piece construction; and

a single support assembly that is sized and configured to support the table top above a surface, the single support assembly including only two legs, the support assembly comprising:

- a first leg including an upper portion and a body portion; and
- a second leg that is pivotally connected to the first leg, the second leg including an upper portion and a body portion;

wherein the upper portion of the first leg is sized and configured to be connected to one of the leg receiving recesses and the upper portion of the second leg is sized and configured to be connected to another of the leg receiving recesses; and

Serial No.: 10/789,859

Filing Date: February 27, 2004

wherein the upper portion of the first leg is capable of being disconnected from one of the leg receiving recesses and connected to another of the leg receiving recesses in order to change the height of the table.

18. (Original) A personal table that is sized and configured to be used by a single person and the table being adjustable in height relative to a support surface, the personal table comprising:

a plastic table top including an upper surface, a lower surface spaced apart from the upper surface, and a side wall;

a drawer connected to the table top;

a single leg assembly that is selectively connected to the table top, the single leg assembly including legs that are pivotally connected in a generally X-shaped configuration, the legs being selectively movable between an extended position and a collapsed position; and

a plurality of receiving members integrally formed in the table top as part of a unitary, one-piece structure, the receiving members being sized and configured to interchangeably receive and retain a portion of the leg assembly in a generally fixed position relative to the table top to allow the height of the personal table to be adjusted.

19. (Original) The personal table as in Claim 18, further comprising an opening in the side wall of the table top, the opening being sized and configured to allow at least a portion of the

Response to Office Action Mailed June 29, 2006

Serial No.:

10/789,859

Filing Date:

February 27, 2004

leg assembly to extend through the opening when the legs are in the collapsed position.

20. (Currently Amended) The personal table as in Claim 19 18, wherein the opening allows the legs to be generally positioned parallel and adjacent to the lower surface of the table top when the legs are in the collapsed position.

21. (Currently Amended) The personal table as in Claim 19 18, wherein the opening is sized and configured to receive and retain the legs in a snap fit configuration when the legs are in the collapsed position.

22. (Currently Amended) The personal table as in Claim 19 18, wherein the opening is sized and configured to facilitate stacking of the table by allowing the legs to be positioned generally parallel and adjacent to the lower surface of the table top when the legs are in the collapsed position.

23. (Original) The personal table as in Claim 18, wherein both of the legs are selectively connected to the table top to allow the height of the table to be adjusted.

Response to Office Action Mailed June 29, 2006

Serial No.:

10/789,859

Filing Date:

February 27, 2004

24. (Original) A personal table that is sized and configured to be used by a single person and the table being adjustable in height relative to a support surface, the personal table comprising:

a plastic table top including an upper surface, a lower surface that is spaced apart from the upper surface, and a side wall;

a drawer slidably connected to the table top;

a single leg assembly that is selectively connected to the table top, the leg assembly including legs that are pivotally connected in a generally X-shaped configuration; the legs being selectively movable between an extended position and a collapsed position; and

an opening in the side wall of the table top that is sized and configured to allow at least a portion of the leg assembly to extend through the opening when the legs are in the collapsed position.

- 25. (Original) The personal table as in Claim 24, wherein the opening allows the legs to be disposed generally parallel and adjacent to the lower surface of the table top when the legs are in the collapsed position.
- 26. (Original) The personal table as in Claim 24, wherein the opening is sized and configured to facilitate stacking of the table by allowing the legs to be positioned generally parallel and adjacent to the lower surface of the table top when the legs are in the collapsed position.

Serial No.: 10/789,859

Filing Date: February 27, 2004

27. (Original) The personal table as in Claim 24, further comprising a plurality of receiving members integrally formed in the table top as part of a unitary, one-piece structure, the receiving members being sized and configured to selectively receive and retain at least a portion of the leg assembly in a generally fixed position relative to the table top.

28. (Original) The personal table as in Claim 24, wherein both of the legs are selectively connected to the table top to allow the height of the table to be adjusted.

Serial No.: 10/789,859

Filing Date: February 27, 2004

29. (Original) A personal table that is sized and configured to be used by a single person, the table being adjustable in height relative to a support surface, the personal table comprising:

a plastic table top including an upper surface, a lower surface that is spaced apart from the upper surface, a side wall, and a hollow interior portion;

a drawer slidably connected to the table top;

a single leg assembly that is selectively connected to the table top, the leg assembly including a pair of legs that are pivotally connected in a generally X-shaped configuration; the legs being selectively movable between an extended position and a collapsed position; and

a plurality of receiving members integrally formed in the table top as part of a unitary, one-piece structure, the receiving members being sized and configured to interchangeably receive and retain at least a portion of the leg assembly in a generally fixed position relative to the table top.